

PRODUCT DATA SHEET

PROLAM Matt

PROLAM is an 80 micron matt transparent promotional grade overlamine aimed to provide greater durability of digital prints with increased resistance to abrasion. Applications include advertising, point of sale, windows, advertising boards and other promotional applications.

APPLICATIONS

- Print protection & abrasion resistance
- Image enhancement
- Point of sale
- Window graphics
- Short term advertising

PERFORMANCE

Material	80 micron transparent PVC film
Color	Matt
Tensile Strength	GB/T1040.1-2006 - Units N/25mm
Adhesive	Transparent permanent
Liner	120 gsm white PEK paper with single PE coating
Dimensional Stability	1mm
Application Temperature	20-30°C
Shelf Life	One year when stored between 20-30°C & 35-65% Humidity
Print Compatibility	Eco solvent, Latex & UV
Durability	Up to one year in Australian conditions
Matched Vinyl	PROSAV & ECOSAV

INSTALLATION

Before applying an overlamine, we suggest you allow 24-48 hours for the print to dry. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.