

## TECHNICAL DATA SHEET

### SLH440 High Gloss Black Back Frontlit Banner

Weight: 440gsm

Property	Test Method	Value	Unit
Weight		440	g/sm
Tensile Strength (warp/weft)	ISO 13934-1 : 1999 C.R.E.STRIP METHOD	710 480	N/50mm
Elongation (warp/weft)	ISO 13934-1 : 1999 C.R.E.STRIP METHOD	16.5 21.5	%
Tearing Strength (warp/weft)	ISO 13934-1 : 2013 C.R.E.SINGLE TOUNGE METHOD	39 26	N
Adhesion Strength (warp/weft)	ISO 2411 : 2000 C.R.E	58 53	N/5cm

**APPLICATIONS**

Internal or external banners on structures, Real estate signage

**AVAILABLE WIDTHS in 50m lengths**

1370mm  
2500mm

**COMPATIBLE INK TECHNOLOGY**

Solvent  
Latex  
UV Curable

**FREE ROLL SLITTING SERVICE AVAILABLE**



Unit 22 / 1029 Manly Rd, Tingalpa QLD 4173  
 P (07) 3890 5414 F (07) 3890 5701  
 ABN 49 163 849 232 ACN 163 849 232

[creativegraphicsupplies.com.au](http://creativegraphicsupplies.com.au)