

PRODUCT DATA SHEET

FROGTACK Matt White PET

FROGTACK is a semi matt white PET window film with an easy apply re-positional white block out adhesive. Suitable for Solvent, Eco Solvent, UV Curable and Latex inks.

APPLICATIONS

- Window graphics
- Point of sale
- Re-positional Stickers and Decals
- Static Cling Substitute

PERFORMANCE

Property	Unit	Spec	Value	Test Method
Appearance	-	Semi-Matte	Semi-Matte	ASTM E284
Base Thickness	µm	120 ± 5	120	ASTM D645
Base Weight	g/m ²	90 ± 5	90	ASTM D646
Total Thickness	µm	275 ± 10	270	ASTM D645
Total Weight	g/m ²	230 ± 10	230	ASTM D646
Gloss	%	60° : 85° :	60° : 85° :	ASTM D2457
Lab	-	L : 92.0 ≤ a : 0.6 ± 1.0 b : -3.4 ± 1.0	L : 92.3 a : 0.8 b : -1.5	ANSI T (D50/2°/Abs/No)
Whiteness	-	91 ± 1	90.89	ASTM E313
VLT	%			KS L 2514
UV CUT	%			JIS A 5759
Peel Strength (Glass 20min)	g/25mm	≤ 13	13	ASTM D903
Peel Strength (Glass 24hour)	g/25mm	≤ 12	12	

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.