

UNIVERSAL PHOTO BASE PAPER 240GSM - FUG/S 240

MATERIAL SPECIFICATIONS SHEET

Description	Super white gloss and semi gloss microporous resin coated photo paper
Applications	Economy photo, premium poster
Comments	Compatible with BOTH Dye and Pigment inks High Colour fidelity Quick drying and wipefast. High batch to batch stability. ICC colour profiles provided
Processing	Best printing results occur in a standard environment of 15-25°C and 40-60% relative humidity. For problem free running, always store the printing medium in the original packaging and protect it from sunlight and moisture.
Environmental	100% virgin fibre sourced from sustainable forests. Nordic Swan Award - the most demanding ecological mark in international paper. Mill maintains ISO14001 Environmental Management System certification - recycles water - uses waste products as energy source - waste and effluent treatment systems in place - no detectible dioxin discharges.
Standard Length	30 metres

Physical properties	Result	Unit	Standard
Weight	235 ± 10	gsm	ISO 536
Thickness	240 ± 10	um	ISO 534
Opacity	96 ± 4.0	%	ISO 2471
Gloss 75 degree face side	49 ± 5.0		ISO 8254
Brightness	98 ± 2.0	%	ISO 2470
Shade L*	94.6		ISO 5033-7
a*	1.3		(D50/10)
b*	-9.4		